



FLANGE TEE

Definition and Application

It is used to make an extension from the main pipe.

- Flange standard according to DIN EN 1092.
- Dimensions standard according to ISO 2531.
- Casting standard according to DIN EN 1693.

Key points

- Flat or patched rubber gaskets are used to seal the flanged parts.
- It enjoys bentonite/primer/bitumen cover as per the order placed by customers to prevent corrosion.
- The holes of all three flanges should be made in such a manner that the parts should be connected in vertical form.

انشعاب				بدنه			
I		e2	L		e1	Size (dn)	Size (DN)
Type B	Type A		Type B	Type A			
165	165	7	330	330	7	80	80
170	175	7	330	360	7.2	80	100
180	180	7.2	330	360	7.2	100	100
200	205	7	360	440	7.8	80	150
205	210	7.2	380	440	7.8	100	150
220	220	7.8	440	440	7.8	150	150
225	235	7	380	520	8.4	80	200
230	240	7.2	400	520	8.4	100	200
245	250	7.8	460	520	8.4	150	200
260	260	8.4	520	520	8.4	200	200
265	---	7	405	---	9	80	250
270	275	7.2	425	700	9	100	250
280	---	7.8	585	---	9	150	250
290	325	8.4	540	700	9	200	250
300	360	9	600	700	9	250	250
295	---	7	425	---	9.6	80	300

ابعاد بر حسب میلی متر می باشد.

انشعاب				بدنه			
I		e2		L		Size (dn)	Size (DN)
Type B	Type A			Type B	Type A		
300	300	7.2		450	800	9.6	100 300
310	---	7.8		505	---	9.6	150 300
320	350	8.4		585	800	9.6	200 300
330	---	9		620	---	9.6	250 300
340	400	9.6		680	800	9.6	300 300
330	325	7.2		470	850	10.2	100 350
340	---	7.8		530	---	10.2	150 350
350	325	8.4		585	850	10.2	200 350
360	---	9		645	---	10.2	250 350
370	---	9.6		645	850	10.2	300 350
380	425	10.2		760	850	10.2	350 350
360	350	7.2		490	90	10.8	100 400
370	---	7.8		550	---	10.8	150 400
380	350	8.4		610	900	10.8	200 400
390	---	9		665	---	10.8	250 400
400	---	9.6		725	---	10.8	300 400

ابعاد بر حسب میلی متر می باشد.

